

Ready2Talk

PA 4 Portable / PA 4 and PA 4+ System

QUICK Instructions

Thank you for purchasing the Ready2Talk PA 4 Portable or PA 4 wired PA system. Connection and use is easy. Ready... here you go!

- 1) With the PA 4 Portable, plug the power into the cigar lighter socket then plug the 3.5mm plug into the iPod or AUX input on your stereo.

With the PA 4, connect the red wire to 12V+ and the black to 12V-, plug the RCA plugs into the rear AUX input on the stereo (or use a RCA to 3.5MM adaptor)

- 2) Change the setting on your stereo to "AUX" and you're good to go.
- 3) Plug the microphone into the socket on the top of the PA 4 model and put on the headset. Place the mic just in front of your mouth (approx. 1" or 3cm)
- 4) Turn on the switch on the front of the PA and the blue LED power indicator light will come on.
- 5) START TALKING and adjust the volume on the stereo to your chosen level. You may need to be slightly higher level than when you listen to the radio and you might want to fade a bit more to the rear speakers if you have any feedback.
- 6) Clean the back of the PA box and a **small** area on the dash board where you want to mount the Velcro for the PA system with Rubbing Alcohol (be careful that the alcohol wipe doesn't remove the dashboard colour) once dry attach the Velcro.
- 7) To play your iPod through the PA 4 Portable or PA 4, set your stereo volume for the correct operation of your PA System... plug your iPod into the 3.5mm socket on the front lower corner of the PA, choose a song on your iPod and start playing. Start at the lowest level on your iPod or iPhone and then adjust to the desired volume with the iPod volume control. You will be able to listen to tunes and talk at the same time.
- 8) Enjoy your PA system. If you have any questions, please give us a call 1 888 695-5351 or drop us a note at info@ready2talk.ca we would be pleased to help.