

Ready2Talk

PA 6 QUICK Instructions

Thank you for purchasing the Ready2Talk PA 6 PA system. Connection and use is easy. Ready... here you go!

- 1) Connect the power plug into the 12 V power socket on the PA 6 and then your vehicle's cigarette lighter / power socket.
- 2) If you want to hardwire the power, cut off the power plug and connect the red wire to 12V+ and the black to 12V-, then connect the 3.5mm plug into the AUX input on your stereo. Remember to install no bigger than a 3A fuse on the red wire.
- 3) Connect the 3.5mm audio cable into the Audio Output socket on the bottom of the PA 6 and the other end into the AUX input on your vehicle **and** change your stereo to the AUX mode.
- 4) Turn on the rocker power switch on the front of the PA and the blue power LED will light.
- 5) Connect the microphone plug into the socket on the top of the PA and put on the headset. Place the mic just in front of your mouth (approx. 1" or 3cm)

IMPORTANT! Please note the bump on the mic socket mates with the corresponding slot on the mic plug to ensure that the 4 pin mic plug is being inserted in the correct position. Failure to do so WILL cause irreparable damage to the microphone. Don't force it!

- 6) START TALKING and adjust the volume on the stereo to your chosen level. You may need to be slightly higher level than when you listen to the radio and you might want to fade a bit more to the rear speakers if you have any feedback.
- 7) To play music from your Mobile Device - Phone / Tablet through the PA 6,
 - Keep your stereo volume setting for the correct operation of your PA
 - Ensure that the in-wire On/Off switch on the microphone is OFF
 - Connect your mobile device into the 3.5mm AUX socket on the front of the PA using a standard 3.5mm to 3.5mm cable
 - **Set your mobile device volume to 50%** and start the music, if you need to adjust the music volume up or down, adjust the phone volume control NOT the stereo volume.
 - Turn the on the microphone and the music volume will cut off automatically. If you want the music to dim rather than cut off, please see "PA 6 Mute Adjustment" PDF on FAQ page. www.ready2talkpa.com

Enjoy your PA system. If you have any questions, please give us a call 1 888 724-5351 or drop us a note at info@ready2talkpa.com we would be pleased to help.

Headset Best Practices

Every once in a while we receive a questions about Ready2Talk headsets, how to wear them and how to best care for them. We hope this answers your questions.

How do I put them on my head?

Here's the trick, the metal headband is designed to go behind your head (not over top) and the curved parts of the headband rest on top of your ears. If it's still too loose or too tight, just bend the width of the metal headband in or out. Don't worry they're tough.




Where do I put the mic foam piece?

First things first... you MUST have a foam sock on your headset, if not, it will sound terrible!

Place the mic pick up about 1" (3cm) away from your mouth and talk normally. Then adjust the volume on your stereo to the correct level. If the mic pick up is too far away the stereo will have to be turned up too much and then you might have feedback issues.

IMPORTANT !!!

Please note the bump on the mic socket mates with the corresponding slot on the mic plug to ensure that the 4 pin mic plug is being inserted in the correct position. Failure to do so WILL cause irreparable damage to the microphone. Do not force it!



Just follow these steps and you'll be Ready2Talk. If you have any questions or want a digital copy of this for your staff, just drop us a note or give us a call. 1 888 724-5351